

# QQ INKELSON



This machine is a multi-channel high performance switching power supply digital class D power amplifier, adopt imported US.A.IR Digital Chip, SMT modular design, the structure is compact and reasonable. Each channel has independently output power supply, even if a particular channel fails, will not affect other channels. All-round protection circuit to deal with excess current overload & short-C, or abnormal DC Voltage Output & Over Heat, 1.5U thin design.

\*70-100V constant pressure output and 4-16 Ohms Output, Balanced, no grounding. 2 or 4 channel for your choose,

\*4 Pcs LED indicators for status display,

\*XLR socket and 6.35mm jack for amplifier link,

\*Protection for short-C, over heat and over load,

\*With Limiter function, music without distortion.

Model	LA-300×2H	LA-400×2H	LA-500×2H	<b>LA-300×4H</b>	LA-400×4H	LA-500×4H
Rated power	300×2W	400×2W	500×2W	<b>300×4W</b>	400×4W	500×4W
Line voltage	70-100V	70-100V	70-100V	<b>70-100V</b>	70-100V	70-100V
Impedance	4-16Ω	4-16Ω	4-16Ω	<b>4-16Ω</b>	4-16Ω	4-16Ω
Dimension(mm)	482*65*405	482*65*405	482*65*405	<b>482*65*405</b>	482*65*405	482*65*405
GW(kg)	7.3	7.3	7.3	<b>13.6</b>	13.6	13.6